



BEARING INDUSTRIA CUSCINETTI S.P.A.



skf SAF 1510 x 1.3/4 T SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SAF 1510 x 1.3/4 T

SAF 1510 x 1.3/4 T Bearing 2D drawings and 3D CAD models

d_a	26.147 mm
D_a	90 mm
C_a	29.794 mm
A_1	60.325 mm
A_2	165.1 mm
S	4.763 mm
b_a	24.606 mm
H	121.841 mm
H_1	63.5 mm
H_2	23.813 mm
J min.	165.1 mm
J max.	177.8 mm
L	209.55 mm
N_1	15.875 mm
R_1	30.163 mm
R_2	14.287 mm
R_G	1/8 NPT
P_G	1/8 NPT
h	28.575 mm
Housing	SAF 510
Bearing	1210 EKTN9
Adapter sleeve assembly	SNW 10x1.3/4
Stabilizing ring	SR-10-8
Taconite seal	TER 21
End plug (suffix Y)	EPR 4



BEARING INDUSTRIA CUSCINETTI S.P.A.

Max. speed for Taconite seal	1800 r/min
P _{60°}	28.9 kN
P _{90°}	17.3 kN
P _{120°}	11.1 kN
P _{150°}	10.1 kN
P _{180°}	12.5 kN
P _a	2.98 kN
Mass pillow block	5.9 kg
Cap bolt	2 x 7/16-14 UNC
Cap bolt recommended tightening torque	61 N · m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.5 in
Initial grease fill	65.205 g