



BEARING INDUSTRIA CUSCINETTI S.P.A.



skf SAW 23536 x 6.1/2 T SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SAW 23536 x 6.1/2 T

SAW 23536 x 6.1/2 T Bearing 2D drawings and 3D CAD models

d_a	165.1 mm
D_a	319.999 mm
C_a	121.818 mm
A_1	180.975 mm
A_2	317.5 mm
S	4.763 mm
b_a	88.106 mm
H	377.825 mm
H_1	190.5 mm
H_2	76.2 mm
J min.	530.225 mm
J max.	600.075 mm
J_1	117.475 mm
L	679.45 mm
N_1	28.575 mm
R_1	114.3 mm
R_2	41.275 mm
R_G	3/4 NPT
P_G	1/4 NPT
h	60.325 mm
Housing	SAW 536
Bearing	23236 CCK/W33
Adapter sleeve assembly	SNW 136x6.1/2
Stabilizing ring	SR-36-30
Taconite seal	TER 149



BEARING INDUSTRIA CUSCINETTI S.P.A.

End plug (suffix Y)	EPR 19
Max. speed for Taconite seal	460 r/min
P _{60°}	234 kN
P _{90°}	140 kN
P _{120°}	84.5 kN
P _{150°}	75.6 kN
P _{180°}	89 kN
P _a	60.5 kN
Mass pillow block	144 kg
Cap bolt	4 x 3/4-10 UNC
Cap bolt recommended tightening torque	203.4 N · m
Cap bolt, SAE grade	5
Eye bolt	2 x 3/8-16 UNC
Appropriate attachment bolt size G	1 in
Initial grease fill	1304.1 g