




BEARING INDUSTRIA CUSCINETTI S.P.A.



skf FSAF 22517 x 3 TLC SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. FSAF 22517 x 3 TLC

FSAF 22517 x 3 TLC Bearing 2D drawings and 3D CAD models

d_a	76.2 mm
D_a	150 mm
C_a	45.796 mm
A_1	88.9 mm
A_2	127 mm
S	4.763 mm
b_a	35.719 mm
H	182.166 mm
H_1	95.25 mm
H_2	31.75 mm
J min.	250.825 mm
J max.	279.4 mm
J_1	53.975 mm
L	330.2 mm
N_1	19.05 mm
R_1	53.975 mm
R_2	22.225 mm
R_G	3/8 NPT
P_G	1/8 NPT
h	34.925 mm
Housing	FSAF 517
Bearing	22217 EK
Adapter sleeve assembly	SNW 17x3
Stabilizing ring	SR-17-14
Labyrinth ring	2 x LOR 54



BEARING INDUSTRIA CUSCINETTI S.P.A.

PosiTrac Plus contact element	2 x B10724-53
End plug (suffix Y)	EPR 9
Max. speed for PosiTrac Plus seal	1950 r/min
P _{60°}	61.4 kN
P _{90°}	36.9 kN
P _{120°}	23.1 kN
P _{150°}	20.9 kN
P _{180°}	25.4 kN
P _a	9.25 kN
Mass pillow block	17.9 kg
Cap bolt	2 x 5/8-11 UNC
Cap bolt recommended tightening torque	149.1 N · m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.625 in
Initial grease fill	110.56 g