



# BEARING INDUSTRIA CUSCINETTI S.P.A.



skf SAFS 23038 KATLC x 6.15/16 SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SAFS 23038 KATLC x 6.15/16

SAFS 23038 KATLC x 6.15/16 Bearing 2D drawings and 3D CAD models

$d_a$	176.213 mm
$D_a$	289.999 mm
$C_a$	89.789 mm
$A_1$	158.75 mm
$A_2$	225.425 mm
$b_a$	69.85 mm
H	338.137 mm
$H_1$	169.875 mm
$H_2$	66.675 mm
J min.	441.325 mm
J max.	488.95 mm
$J_1$	95.25 mm
L	558.8 mm
$N_1$	28.575 mm
$R_1$	104.775 mm
$R_2$	33.337 mm
$R_G$	3/4 NPT
$P_G$	1/4 NPT
h	47.625 mm
Housing	SAFS 038 KA
Bearing	23038 CCK/W33
Adapter sleeve assembly	SNW 3038x6.15/16
Stabilizing ring	2 x 38151-38
Labyrinth ring	2 x LOR 155
PosiTrac Plus contact	2 x B10724-155



## BEARING INDUSTRIA CUSCINETTI S.P.A.

element	
End plug (suffix Y)	EPR 21
Max. speed for PosiTrac Plus seal	825 r/min
P <sub>60°</sub>	345 kN
P <sub>90°</sub>	207 kN
P <sub>120°</sub>	133 kN
P <sub>150°</sub>	120 kN
P <sub>180°</sub>	145 kN
P <sub>a</sub>	42.9 kN
Mass pillow block	121 kg
Cap bolt	7/8-9 UNC
Cap bolt recommended tightening torque	813.5 N · m
Cap bolt, SAE grade	8
Eye bolt	2 x 3/8-16 UNC
Appropriate attachment bolt size G	1 in
Initial grease fill	793.8 g