




# BEARING INDUSTRIA CUSCINETTI S.P.A.



skf SSAFS 23026 KAT x 4.7/16 SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SSAFS 23026 KAT x 4.7/16

SSAFS 23026 KAT x 4.7/16 Bearing 2D drawings and 3D CAD models

$d_a$	112.713 mm
$D_a$	200 mm
$C_a$	62.789 mm
$A_1$	120.65 mm
$A_2$	231.775 mm
$b_a$	51.594 mm
H	244.475 mm
$H_1$	125.425 mm
$H_2$	52.388 mm
L	419.1 mm
$R_1$	73.025 mm
$R_2$	31.75 mm
$R_G$	3/8 NPT
$P_G$	1/4 NPT
h	40.922 mm
Housing	SSAFS 026 KA
Bearing	23026 CCK/W33
Adapter sleeve assembly	SNW 3026x4.7/16
Stabilizing ring	2 x 38151-26
Taconite seal	TER 117
End plug (suffix Y)	EPR 15
Max. speed for Taconite seal	700 r/min
$P_{60^\circ}$	178 kN
$P_{90^\circ}$	107 kN
$P_{120^\circ}$	66.7 kN



## BEARING INDUSTRIA CUSCINETTI S.P.A.

$P_{150^\circ}$	59.6 kN
$P_{180^\circ}$	72.5 kN
$P_a$	20.2 kN
Mass pillow block	52.2 kg
Cap bolt	5/8-11 UNC
Cap bolt recommended tightening torque	298.3 N · m
Cap bolt, SAE grade	8
Eye bolt	2 x 3/8-16 UNC
Initial grease fill	232.47 g