




BEARING INDUSTRIA CUSCINETTI S.P.A.



skf SAF 22632 x 5.3/8 TLC SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SAF 22632 x 5.3/8 TLC

SAF 22632 x 5.3/8 TLC Bearing 2D drawings and 3D CAD models

d_a	136.525 mm
D_a	339.999 mm
C_a	123.8 mm
A_1	190.5 mm
A_2	273.05 mm
S	4.763 mm
b_a	87.313 mm
H	401.637 mm
H_1	200.025 mm
H_2	79.375 mm
J min.	549.275 mm
J max.	619.125 mm
J_1	114.3 mm
L	711.2 mm
N_1	34.925 mm
R_1	120.65 mm
R_2	42.069 mm
R_G	1 NPT
P_G	1/4 NPT
h	68.263 mm
Housing	SAF 632
Bearing	22332 CCK/W33
Adapter sleeve assembly	SNW 132x5.3/8
Stabilizing ring	SR-38-32
Labyrinth ring	2 x LOR 129



BEARING INDUSTRIA CUSCINETTI S.P.A.

PosiTrac Plus contact element	2 x B10724-130
End plug (suffix Y)	EPR 16
Max. speed for PosiTrac Plus seal	1050 r/min
P_{60°	290 kN
P_{90°	173 kN
P_{120°	107 kN
P_{150°	94.3 kN
P_{180°	113 kN
P_a	54.3 kN
Mass pillow block	178 kg
Cap bolt	4 x 7/8-9 UNC
Cap bolt recommended tightening torque	271.2 N · m
Cap bolt, SAE grade	5
Eye bolt	2 x 1/2-13 UNC
Appropriate attachment bolt size G	1.25 in
Initial grease fill	1672.65 g