




BEARING INDUSTRIA CUSCINETTI S.P.A.



skf SAFS 22640 x 7.1/4 SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SAFS 22640 x 7.1/4

SAFS 22640 x 7.1/4 Bearing 2D drawings and 3D CAD models

d_a	184.15 mm
D_a	419.999 mm
C_a	147.803 mm
A_1	228.6 mm
A_2	317.5 mm
S	4.763 mm
b_a	103.188 mm
H	495.3 mm
H_1	250.825 mm
H_2	101.6 mm
J min.	666.75 mm
J max.	749.3 mm
J_1	139.7 mm
L	869.95 mm
N_1	41.275 mm
R_1	163.512 mm
R_2	50.8 mm
R_G	1 NPT
P_G	1/4 NPT
h	87.313 mm
Housing	SAFS 640
Bearing	22340 CCK/W33
Adapter sleeve assembly	SNW 140x7.1/4
Stabilizing ring	SR-0-40
Labyrinth ring	2 x LOR 666



BEARING INDUSTRIA CUSCINETTI S.P.A.

End plug (suffix Y)	EPR 21
Bearing limiting speed	1500 r/min
P _{60°}	669 kN
P _{90°}	400 kN
P _{120°}	249 kN
P _{150°}	222 kN
P _{180°}	267 kN
P _a	82.7 kN
Mass pillow block	431 kg
Cap bolt	4 x 1 1/2-6 UNC
Cap bolt recommended tightening torque	4284.4 N · m
Cap bolt, SAE grade	8
Eye bolt	2 x 1/2-13 UNC
Appropriate attachment bolt size G	1.5 in
Initial grease fill	3515.4 g