




BEARING INDUSTRIA CUSCINETTI S.P.A.



skf FSAF 22313 T SAF and SAW pillow blocks with bearings with a cylindrical bore

Bearing No. FSAF 22313 T

FSAF 22313 T Bearing 2D drawings and 3D CAD models

d_a	65 mm
d_b	77.787 mm
d_c	61.913 mm
D_a	140 mm
C_a	57.785 mm
A_1	88.9 mm
A_2	209.55 mm
S	4.763 mm
b_a	40.481 mm
H	167.481 mm
H_1	88.9 mm
H_2	31.75 mm
J min.	244.475 mm
J max.	279.4 mm
J_1	53.975 mm
L	330.2 mm
N_1	19.05 mm
R_1	53.181 mm
R_2	21.431 mm
R_G	3/8 NPT
P_G	1/8 NPT
h	35.719 mm
Housing	FSAF 313
Bearing	22313 E
Lock nut	N 13



BEARING INDUSTRIA CUSCINETTI S.P.A.

Lock washer	W 13
Stabilizing ring	SR-16-13
Taconite seal (d_b shaft position)	TER 55
Taconite seal (d_c shaft position)	TER 37
End plug (suffix Y)	EPR 7
Max. speed for Taconite seal	1000 r/min
P_{60°	60.5 kN
P_{90°	36 kN
P_{120°	21.8 kN
P_{150°	19.6 kN
P_{180°	23.1 kN
P_a	14.7 kN
Mass pillow block	17 kg
Cap bolt	2 x 5/8-11 UNC
Cap bolt recommended tightening torque	298.3 N · m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.625 in
Initial grease fill	87.885 g