



BEARING INDUSTRIA CUSCINETTI S.P.A.



SAF 22326 Bearing 2D drawings and 3D CAD models

5.118 Inch | 130 Millimeter x 8.75 Inch | 222.25
Millimeter x 6.688 Inch | 169.875 Millimeter skf
SAF 22326 SAF and SAW pillow blocks with
bearings with a cylindrical bore

Bearing No. SAF 22326

Category	Pillow Block Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	100.33
EAN	7316577021236
Product Group	M06288
Number of Mounting Holes	2
Mounting Method	Shaft Mount
Housing Style	2 Bolt Pillow Block
Rolling Element	Spherical Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Expansion
Mounting Bolts	1 Inch
Relubricatable	Yes
Insert Part Number	22326 CC/W33
Seals	Labyrinth
Housing Configuration	2 Piece Split
Inch - Metric	Metric
Other Features	Double Row Heavy Duty
Long Description	2 Bolt Pillow Block; 130MM Bore; 169.875MM Base to Center Height; Shaft Mount Mount; Spherical Roller Bearing; 441.325MM



BEARING INDUSTRIA CUSCINETTI S.P.A.

	Minimum Bolt Spacing; 488.95MM Bolt Spacing Maximum; Relubricatable; Cast Iron;
Category	Pillow Block
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Pillow Block
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	SAF 22326
Weight / LBS	221
D	8.75 Inch 222.25 Millimeter
Nominal Bolt Center to Center	18.3 Inch 464.8 Millimeter
Bolt Spacing Maximum	19.25 Inch 488.95Millimeter
Bolt Spacing Minimum	17.375 Inch 441.325Millimeter
B	6.688 Inch 169.875 Millimeter
Actual Bolt Center to Center	0 Inch 0Millimeter
d	5.118 Inch 130 Millimeter
d _a	130 mm
d _b	149.225 mm
d _c	125.412 mm
D _a	279.999 mm
C _a	102.794 mm
A ₁	158.75 mm
A ₂	222.25 mm
S	4.763 mm
b _a	72.231 mm
H	336.55 mm



BEARING INDUSTRIA CUSCINETTI S.P.A.

H_1	169.875 mm
H_2	66.675 mm
J min.	441.325 mm
J max.	488.95 mm
J_1	95.25 mm
L	558.8 mm
N_1	28.575 mm
R_1	104.775 mm
R_2	33.337 mm
R_G	3/4 NPT
P_G	1/4 NPT
h	61.913 mm
Housing	SAF 326
Bearing	22326 CC/W33
Lock nut	AN 26
Lock washer	W 26
Stabilizing ring	SR-0-26
Labyrinth ring (d_b shaft position)	LOR 136
Labyrinth ring (d_c shaft position)	LOR 122
End plug (suffix Y)	EPR 27
Bearing limiting speed	2400 r/min
P_{60°	226 kN
P_{90°	136 kN
P_{120°	85.9 kN
P_{150°	78.3 kN
P_{180°	94.3 kN
P_a	60.9 kN
Mass pillow block	100 kg
Cap bolt	4 x 3/4-10 UNC
Cap bolt recommended tightening torque	203.4 N · m



BEARING INDUSTRIA CUSCINETTI S.P.A.

Cap bolt, SAE grade	5
Eye bolt	2 x 3/8-16 UNC
Appropriate attachment bolt size G	1 in
Initial grease fill	793.8 g